



TO: Wheaton Park District  
102 E. Wesley Street  
Wheaton, IL 60187  
Michael Benard

RE: Wheaton Park District  
Community Center Renovation  
1777 South Blanchard  
Wheaton, IL 60189

**Change Order Request No. 9.R2**

Date: October 26, 2022

We hereby agree to make the change(s) specified below:

| Item # |   | Amount      |
|--------|---|-------------|
| 1      | Furnish LVT at old VCT, install transition, cut existing wood floor straight, float floor | \$ 2,556.29 |
| 2      | Demo existing VCT   | \$ 135.00   |
|        | Includes new base   |             |
|        |   |             |

|                                   |       |                    |
|-----------------------------------|-------|--------------------|
| Subtotal                          |       | \$ 2,691.29        |
| Overhead & Profit                 | 10.0% | \$ 269.13          |
| <b>Total Change Order Request</b> |       | <b>\$ 2,960.42</b> |

ACCEPTED. The above prices and specifications are satisfactory and hereby accepted. All work to be performed under same terms and conditions as specified in original contract.

  
 Date: 11/17/22  
 Michael Benard- Wheaton Park District

No signature required by ECS  
 David W. Hillstrom - Efraim Carlson & Son



14052 Petronella Drive • Suite 105 Libertyville, IL 60048  
 847.573.1888  
 Fax 847.573.0188  
 www.efraimcarlson.com

# JOHNSON FLOOR COMPANY, INC.

Date: September 22<sup>nd</sup>, 2022

Attn: Mr. Matt Hillstrom  
President  
Efraim Carlson & Son  
14052 Petronella Dr. Suite 105  
Libertyville, IL

Re: Wheaton Park District – Community Center Remodeling  
1777 South Blanchard St.  
Wheaton, IL

Item: CO Request for Flooring and Base, Room SB08 Storage Closet

Matt,

Please see the T&M breakdown for the furnishing of new luxury vinyl tile and wall base in room SB08 Storage Closet:

## **Add LVT and Base in Room SB08 Storage Closet**

### **Material @ Cost**

|   |          |
|---|----------|
| 212 sqft Mohawk Group <i>Reforestation</i> , color: 220 Bridal Veil, 9" x 59" @ \$3.53/sqft | \$748.36 |
| 2 gallons pressure sensitive adhesive @ \$120.00/4 gallon pail                              | \$60.00  |
| 54 LF Tarkett 4" wall base @ \$0.89/LF  | \$48.06  |
| ½ gallon of base adhesive @ \$15.00/gallon  | \$7.50   |
| 8 LF Tarkett CTA-XX-J @ \$4.00/LF   | \$32.00  |
| 4 bags Ardex <i>Feather Finish</i> @ \$14.79/bag  | \$59.16  |
| Misc. materials to install LVT  | \$15.00  |

|                   |                |
|-------------------|----------------|
| 10% mark up       | \$97.01        |
| Freight           | <u>\$74.20</u> |
| Material subtotal | \$1141.29      |

### **Labor**

|   |          |
|---|----------|
| 4 hours of labor to prep and build up floor for hardwood transition @ \$141.50/hour | \$566.00 |
| 5 hours of labor to install LVT and transitions @ \$141.50                          | \$707.50 |
| 1 hours of labor to install base @ \$141.50/hour                                    | \$141.50 |

|                  |                                |
|------------------|--------------------------------|
| <b>Total Add</b> | <b><u><u>\$2556.29</u></u></b> |
|------------------|--------------------------------|

Please issue a change order in the amount of **\$2556.29** for the furnishing and installation of the additional LVT in the storage room stated above. Please let me know if you have any questions. Thank you.

Michael Johnson



## Wheeled Traffic Transitions

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Wheel Traffic Transitional Mouldings

1.2. **Manufacturer:**

Tarkett North America                      Phone:     (800) 899-8916  
30000 Aurora Rd.                                (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Wheel Traffic Transitional Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. All Wheel Traffic Transitional Mouldings comply with A.D.A. requirements of Section 4.5.2 Changes of Level.

1.3.2. **Styles:**

**CTA-XX-H:** 1/4" (6.35 mm) to 1/8" (3.18 mm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-HL:** 1/4" (6.35 mm) to 1/8" (3.18 mm) material, 4" (10.16 cm) cap with 3-1/4" (8.26 cm) wide support base, wheel traffic design (1:20 slope)

**CTA-XX-HT:** 1/4" (6.35 mm) to .080" (2.0 mm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-J:** 1/4" (6.35 mm) material to floor, 2-1/2" (6.35 cm) cap with 2-1/8" (5.4 cm) wide support base

**CTA-XX-JL:** 1/4" (6.35 mm) material to floor, 4" (10.16 cm) cap with 3-5/8" (9.21 cm) wide support base, wheel traffic design

**CTA-XX-K:** 3/8" (9.53 mm) to 1/8" (3.18 mm) materials, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design (1:8 slope)

**CTA-XX-L:** 3/8" (9.53 mm) to 1/4" (6.35 mm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-M:** 1/4" (10.16 cm) to 1/4" (10.16 cm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-N:** 1/8" (3.17 cm) to 1/8" (3.17 cm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-P:** 3/8" (9.53 mm) material to floor, 2-1/2" (6.35 cm) cap with 2-1/8" (5.4 cm) wide support base, wheel traffic design

**CTA-XX-PL:** 3/8" (9.53 mm) to floor, 4" (10.16 cm) cap with 3-5/8" (9.2 cm) wide support base, wheel traffic design

**CTA-XX-Q:** 1/2" (12.7 mm) to floor, 4" (10.16 cm) cap with 3-5/8" (9.2 cm) wide support base, wheel traffic design

**CTA-XX-X:** 1/8" (3.17 mm) to .080" (2 mm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-Y:** .080" (2 mm) to .080" (2 mm) material, 2-1/2" (6.35 cm) cap with 1-3/4" (4.45 cm) wide support base, wheel traffic design

**CTA-XX-Z:** 3/8" (9.53 mm) to .080" (2 mm) material, 2-1/2" (10.16 cm) cap with 1-3/4" (9.2 cm) wide support base, wheel traffic design

### 1.4. Physical Characteristics:

**Length:** 12 ft. (3.66 m)

**Packaging:** 10 lengths [120 ft. (36.58 m)] per carton, except CTA-HL and CTA-Q = 5 lengths [60 ft. (18.3 m)] per carton; CTA-PL = 6 lengths [72 ft. (21.9 m)] per carton.

## 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Hardness:** ASTM D 2240 - Not less than 85 Shore A

2.2. **Abrasion Resistance:** ASTM D 3389 - 0.22 mg/cycle

2.3. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.4. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

## 3. INSTALLATION

3.1. See Tarkett Wheeled Traffic Transition installation and maintenance instructions for complete details.

### 3.2. Adhesives:

- **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)  
Application: Brush or roller  
Approximate coverage:  
1 Quart (0.95 liters) – 24 to 36 sq. ft.  
1 Gallon (3.79 liters) – 100 to 150 sq. ft.
- **Other adhesives:** 925, 926, 959, 965, 996 Two-part epoxy, and 975 two-part urethane.

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.



### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Wheeled Traffic Transition Installation & Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

---

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)